

Product datasheet

Specifications



earth-leakage module Compact Vigi
MH - 30..10000 mA - 440..550 V - 3
poles

31533

! Discontinued

Main

Range Of Product	NR100...250 NS100...250
Range	ComPact
Product Or Component Type	Earth leakage add-on block
Device Application	Wiring
Range Compatibility	ComPact Compact NR circuit breaker ComPact ComPact NS circuit breaker
Poles Description	3P
Protected Poles Description	3t
[In] Rated Current	250 A
Earth-Leakage Add-On Module Name	MH
Earth-Leakage Protection Class	Class A
Residual Earth-Leakage Sensitivity Adjustment Type	Adjustable 5 settings
[I _{Δn}] Residual Earth-Leakage Sensitive Adjustment	0.03...10 A
Residual Earth-Leakage Time Delay Adjustment Type	Adjustable
[Δt] Residual Earth-Leakage Time Delay Adjustment	0 ms 60 ms 310 ms 150 ms

Complementary

Network Type	AC
Network Frequency	50/60 Hz
Mounting Support	DIN rail
Electrical Connection To Mcb	By screws
[U _e] Rated Operational Voltage	440...550 V AC 50/60 Hz conforming to IEC 60947-2
Earth-Leakage Protection	With
Maximum Breaking Time	800 ms
Overvoltage Category	Class II
Height	105 mm
Width	236 mm
Depth	86 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Net Weight	2.8 kg
------------	--------

Environment

Electrical Shock Protection Class	Class II
Standards	IEC 60947-2
Product Certifications	ASTA KEMA ASEFA LCIE

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Contractual warranty

Warranty	18 months
----------	-----------