


Product datasheet

Specifications



Unica - SAT single shield socket - male passage - ivory

MGU3.463.25

 **Discontinued on:** Jun 15, 2023 AD

 **Discontinued**

Main

| | |
|---------------------------|----------------------------|
| Range | Unica |
| Aesthetic Name | Unica (standard aesthetic) |
| Product Or Component Type | SAT socket |
| Device Presentation | Mechanism |
| Tv Socket Type | Intermediate |
| Colour Tint | Ivory |

Complementary

| | |
|----------------------------|-----------------------------|
| Sat Connector | Male IEC 9.52 mm |
| Maximum Branch Attenuation | TV <1 dB |
| Path Attenuation | 11 dB TV signal5...2150 MHz |
| Dc Current Flow | No |
| Number Per Line | 4 |
| Number Of Modules | 2 modules |
| Material | ASA + PC: mechanism cover |
| Fixing Mode | Clip-in |
| Depth | 28 mm |
| Width | 45 mm |
| Height | 45 mm |
| Embedding Depth | 18 mm |
| Net Weight | 0.073 kg |

Environment

| | |
|---------------------------------------|------------|
| Ip Degree Of Protection | IP20 |
| Ik Degree Of Protection | IK01 |
| Ambient Air Temperature For Operation | 15...35 °C |
| Ambient Air Temperature For Storage | 0...35 °C |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|------------------------------|---|
| Environmental Characteristic | UV resistant Alcohol Oil Liquid soap Acetone Petrol Window-cleaning fluid Bleach |
| Standards | R.D. 1/1998 UNE 20-523-79 (2e) EMC directive R.D. 279/1999 EN 50083-1 DIN 45325 EN 50083-2 EN 50083-4 DIN 45330 |

Packing Units

| | |
|------------------------------|---------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 6.7 cm |
| Package 1 Width | 4.4 cm |
| Package 1 Length | 6.8 cm |
| Package 1 Weight | 55 g |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 10 |
| Package 2 Height | 4.4 cm |
| Package 2 Width | 13.6 cm |
| Package 2 Length | 33.5 cm |
| Package 2 Weight | 550 kg |
| Unit Type Of Package 3 | S01 |
| Number Of Units In Package 3 | 20 |
| Package 3 Height | 15 cm |
| Package 3 Width | 15 cm |
| Package 3 Length | 40 cm |
| Package 3 Weight | 1100 kg |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

| | |
|--|---|
|  Reach Free Of Svhc | |
|  Toxic Heavy Metal Free | |
|  Mercury Free | |
|  Rohs Exemption Information | Yes |
| Reach Regulation | REACH Declaration |
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |